

***lisa* SHAKE™**

ELISA Plate Shaker-Incubator



CE

## Features

- Simultaneous orbital shaking & incubation operation
- Buzzer indication on completion of incubation
- Indication of Remaining Time
- Display of temperature on pressing TEMP Key

## Technical Specifications

**Operating Modes** : Shaker, Incubator, Shaker & Incubator

**Operating Position** : On horizontal flat, rigid and vibration free surface

**Incubation Time** : 1 to 999 min

### TEMPERATURE CONTROL

**Temperature Range** : 37<sup>o</sup> C to 42<sup>o</sup> C

**Resolution** : 1<sup>o</sup> C

### SHAKER

**Frequency** : 400 to 700 RPM

### STORAGE CONDITIONS

**Temperature** : From - 10<sup>o</sup> C to 35<sup>o</sup> C

**Relative Humidity** : Up to 80%


### OPERATING CONDITIONS

**Temperature** : From + 18<sup>o</sup> C to 32<sup>o</sup> C

**Relative Humidity** : Up to 80%

**Dimensions in mm (lxbxh)** : 280 X 250 X 160 (Approx)

**Weight** : 3 Kg (Approx)



RPM 400 TO 700



Incubator



Shaker

*Due to continuous development, specifications are subject to change without prior notice.*