

readwell TOUCH™

Automatic ELISA Plate Analyser



CE

Reads Micro Plates Precisely

Features

- Accommodates different microplate geometries U, V & Flat
- Plate shaking facility with variable speed and duration
- Ability to read plate within seconds
- Digital light control with unique circuit for long lamp life
- Bichromatic readings
- Flexible controls and calibrators positioning
- Storage of calibration curves & controls
- External printer connectivity
- Patient report with PID & name
- Various Graph curve fit mode : Linear, Point to Point, 4 parameter log regression, Cubic Spline, Polynomial with scales such as Log Abs / Conc, Logit Abs / Log Conc, Abs / Conc, Log Abs / Log Conc etc.
- Matrix mode for result printing
- Storage of plate results
- Data transfer to computer with easy view of results in Excel format

Technical Specifications

OPTICAL SYSTEM

Linear measurement range : 0.000 to 3.500 absorbance units(A)

Photometric accuracy : $\pm 2\%$ or 0.007 whichever is higher from 0 to 1.5 A,
 $\pm 3\%$ from 1.5 A to 3.5 A

Drift : <0.005 A/hr

Resolution : 0.001

Light source : Halogen

FILTERS

Type of filter : High quality narrow band interference

Wavelength : 405, 450, 492, 630 nm & two optional

Half bandwidth : < 10 nm

Selection : Automatic by stepper motor

MEMORY

Programs : 250 tests

Results : 9600 patient results retrieval Assay wise, Patient wise

PRINTER : On board thermal 52 columns, maintenance free

DISPLAY

Human machine interface : TOUCH PANEL & KEYPAD,
7" Graphics Color Display

POWER

Voltage : 115 – 230 Volts $\pm 10\%$, 50 – 60 Hz

COMPUTER INTERFACE

RS232 Serial Port : 9600 baud, 8 data, 1 stop, no parity bits

USB

ANALYSIS MODES : Absorbance, Cut-off, Multi-standard,
 $\%$ Absorbance, Single standard, Uptake, Ratio

Curve Plotting : Graphical representation on printer & display


Plate Carrier Movement : Precisely through stepper motor

Dimensions in mm (lxbxh) : 405 x 380 x 280 (Approx)


Weight : 10 kgs. (Approx)



Printer



Display



Graph

Due to continuous development, specifications are subject to change without prior notice.